NEX®2 12ga (Steel) Knockout Maximum Spans (feet-inches)

		0 psf Snow*		20 psf Snow*		40 psf Snow*		60 psf Snow*		100 psf Snow*	
Exposure	Basic Wind Speed	Interior	Edge	Interior	Edge	Interior	Edge	Interior	Edge	Interior	Edge
B	90 mph	11'-9"	11'-9"	9'-0"	9'-0"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	100 mph	11'-9"	11'-4"	9'-0"	9'-0"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	110 mph	11'-9"	10'-4"	9'-0"	8'-10"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
(suburbs)	120 mph	11'-1"	9'-5"	9'-0"	8'-3"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	130 mph	10'-3"	8'-9"	8'-10"	7'-9"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	140 mph	9'-6"	8'-1"	8'-4"	7'-3"	6'-3"	6'-1"	5'-1"	5'-1"	3'-9"	3'-9"
	150 mph	8'-11"	6'-5"	7'-10"	6'-3"	6'-3"	5'-9"	5'-1"	5'-1"	3'-9"	3'-9"
C (rural)	90 mph	11'-9"	10'-8"	9'-0"	9'-0"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	100 mph	11'-3"	9'-7"	9'-0"	8'-4"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	110 mph	10'-3"	8'-9"	8'-10"	7'-9"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	120 mph	9'-5"	8'-0"	8'-3"	7'-2"	6'-3"	6'-0"	5'-1"	5'-1"	3'-9"	3'-9"
	130 mph	8'-8"	6'-1"	7'-8"	6'-1"	6'-3"	5'-8"	5'-1"	5'-1"	3'-9"	3'-9"
	140 mph	8'-1"	5'-2"	7'-3"	5'-2"	6'-1"	5'-2"	5'-1"	5'-0"	3'-9"	3'-9"
	150 mph	6'-4"	4'-6"	6'-2"	4'-6"	5'-9"	4'-6"	5'-1"	4'-6"	3'-9"	3'-9"
	90 mph	11'-6"	9'-9"	9'-0"	8'-6"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
	100 mph	10'-4"	8'-10"	8'-11"	7'-9"	6'-3"	6'-3"	5'-1"	5'-1"	3'-9"	3'-9"
D The second second	110 mph	9'-5"	8'-0"	8'-3"	7'-2"	6'-3"	6'-0"	5'-1"	5'-1"	3'-9"	3'-9"
(shoreline)	120 mph	8'-8"	6'-0"	7'-8"	6'-0"	6'-3"	5'-8"	5'-1"	5'-1"	3'-9"	3'-9"
(only only)	130 mph	8'-0"	5'-1"	7'-2"	5'-1"	6'-0"	5'-1"	5'-1"	4'-11"	3'-9"	3'-9"
	140 mph	6'-1"	4'-4"	6'-1"	4'-4"	5'-8"	4'-4"	5'-1"	4'-4"	3'-9"	3'-9"
	150 mph	5'-4"	3'-10"	5'-4"	3'-10"	5'-4"	3'-10"	5'-0"	3'-10"	3'-9"	3'-9"

Assumptions:

Light Detailing = Low Basic Wind Speeds & Minimal Snow Loads
Medium Detailing = Moderate Basic Wind Speeds & Snow Loads
Heavy Detailing = Increased Basic Wind Speeds & High Snow Loads



^{*}Roof Snow Load listed, linear interpolation is permitted

^{**}In most cases, edge zone is approximately 3 feet from ridge line and eaves

⁻PhotoVoltaic Module length is 72" or less

⁻Building height must be less than or equal to 30 feet

⁻Maximum cantilever is 2'-6"/1'-6"/0'-9", respectively

⁻Rail splices not permitted immediately over supports or within middle 1/3 of span

⁻For installations that do not conform to the assumptions listed above contact Zilla for a more complete engineering analysis.